## Amendments to the Claims:

The following listing of claims replaces all prior versions and listing of claims in the application.

## Listing of Claims:

1. (Currently Amended) An exercise apparatus comprising:

a first treadle assembly providing a first moving surface, the first treadle including a front and a rear, the first treadle assembly arranged to pivot at the rear thereof;

a second treadle assembly providing a second moving surface, the second treadle including a front and a rear, the second treadle assembly arranged to pivot at the rear thereof;

an interconnection assembly operably connecting the first treadle assembly and the second treadle assembly such that pivotal movement of the first treadle assembly in a first direction causes pivotal movement of the second treadle assembly in a second direction opposite of the first direction; and

at least one resistance element operably coupled with the interconnection assembly.

(Original) The exercise apparatus of claim 1 wherein:

the first moving surface comprises a first roller and a second roller and an endless belt in rotatable engagement with the first and second roller; and

the second moving surface comprises a third roller and a fourth roller and a second endless belt in rotatable engagement with the third and fourth roller.

 (Original) The exercise apparatus of claim 1 wherein the interconnection assembly comprises:

a rocker arm arranged to pivot about a first pivot point.

- 4. (Original) The exercise device of claim 3 wherein the rocker arm comprises a first portion and a second portion to either side of the first pivot point, the first portion coupled with the first treadle assembly and the second portion coupled with the second treadle assembly.
- 5. (Original) The exercise device of claim 4, wherein the interconnection assembly further comprises:
- a first rod connected between the first portion of the rocker arm and the first treadle assembly; and

a second rod connected between the second portion of the rocker arm and the second treadle assembly.

6.	(Currently Amended) An exercise apparatus comprising:
a firs	t treadle assembly providing a first moving surface, the first treadle assembly
arranged to	pivot;
a sec	cond treadle assembly providing a second moving surface, the second treadle
assembly ar	ranged to pivot;
an in	terconnection assembly operably connecting the first treadle assembly and the
second treat	dle assembly such that pivotal movement of the first treadle assembly in a first
direction cau	uses pivotal movement of the second treadle assembly in a second direction
opposite of t	he first direction; and
at lea	ast one resistance element operably coupled with the interconnection assembly:
wher	ein the interconnection assembly comprises a rocker arm arranged to pivot about a
first pivot po	int, the rocker arm comprising a first portion and a second portion to either side of
the first pivo	t point, the first portion coupled with the first treadle assembly and the second
portion coup	oled with the second treadle assembly; and

wherein the interconnection assembly further comprises a first rod connected between the first portion of the rocker arm and the first treadle assembly and a second rod connected between the second portion of the rocker arm and the second treadle assembly. The exercise device of claim 5-wherein the first rod eemprises-comprising a turnbuckle and the second rod eemprises-comprising a turnbuckle.

 (Withdrawn) The exercise apparatus of claim 1 further comprising a frame structure, and wherein the interconnection assembly comprises:

at least one pulley connected with the frame structure;

at least one cable operably supported between the at least one pulley, the first treadle assembly and the second assembly.

8. (Withdrawn) The exercise device of claim 7 wherein the at least one pulley comprises:

at least one first pulley connected with the frame structure above the first treadle assembly; and

at least one second pulley connected with the frame structure above the second treadle assembly.

(Withdrawn) The exercise device of claim 8 wherein:

the first treadle assembly includes a third pulley:

the second treadle assembly includes a fourth pulley; and

the at least one cable is operably supported by the third pulley and the fourth pulley.

- (Withdrawn) The exercise apparatus of claim 1 wherein the at least one resistance element comprises a rotationally elastic member.
- (Withdrawn) The exercise apparatus of claim 1 wherein the resistance element comprises a clutch.
- 12. (Withdrawn) The exercise apparatus of claim 11 wherein the interconnection assembly comprises a rocker arm adapted to pivot about a pivot axis, and wherein the clutch comprises a first clutch plate operably connected with the rocker arm and a second clutch plate adapted to engage the first clutch plate to provide a resistance between the first and second clutch plates.
- 13. (Withdrawn) The exercise apparatus of claim 12 wherein the second clutch plate is adjustably arranged to provide an adjustable resistance between the first clutch plate and the second clutch plate.
- 14. (Withdrawn) The exercise apparatus of claim 13 wherein the second clutch plate is supported by a pivotable bracket, the pivotable bracket comprising a biasing member to adjust the second clutch.
- (Withdrawn) The exercise apparatus of claim 14 further comprising a spring member arranged to urge the second clutch plate against the first clutch plate.
- 16. (Withdrawn) The exercise apparatus of claim 3 further comprising a frame and wherein the resistance element comprises:

at least one spring element operably coupled between the frame and the rocker arm.

(Withdrawn) The exercise apparatus of claim 16 wherein the at least one spring
is coupled to the rocker arm distally from the first pivot point.

18. (Withdrawn) The exercise apparatus of claim 3 further comprising: a frame:

the rocker arm comprises a pivot axle:

the resistance element comprises a pulley operably coupled with the pivot axle; and at least one spring operably coupled between the pulley and the frame.

19. (Currently Amended) An exercise apparatus comprising:

a first treadle assembly providing a first moving surface, the first treadle assembly arranged to pivot;

a second treadle assembly providing a second moving surface, the second treadle assembly arranged to pivot;

an interconnection assembly operably connecting the first treadle assembly and the

an interconnection assembly operably connecting the first treadle assembly and the second treadle assembly such that pivotal movement of the first treadle assembly in a first direction causes pivotal movement of the second treadle assembly in a second direction opposite of the first direction;

at least one resistance element operably coupled with the interconnection assembly;

wherein the interconnection assembly comprises a rocker arm arranged to pivot about a first pivot point. The exercise apparatus of claim 3 further comprising:

——wherein the rocker arm comprises a pivot axle; and a brake operably coupled with the pivot axle.

- (Previously Presented) The exercise apparatus of claim 19 wherein the brake comprises a hydraulic device.
- 21. (Withdrawn Currently Amended ) An exercise apparatus comprising: a first treadle assembly providing a first moving surface including a first roller and a second roller and an endless belt in rotatable engagement with the first and second roller, the first treadle including a front and a rear, the first treadle assembly arranged to pivot at the rear thereof;

a resistance device comprising a first disk and a first strap connected between the first treadle assembly, around the disk, and with the base frame.

(Withdrawn - Currently Amended) An exercise apparatus comprising:
 a frame:

a first treadle assembly providing a first moving surface, the first treadle including a front

and a rear, the first treadle assembly arranged to pivot at the rear thereof;

a second treadle assembly providing a second moving surface, the second treadle including a front and a rear, the second treadle assembly arranged to pivot at the rear thereof;

an interconnection assembly operably coupled between the first treadle assembly and with the second treadle assembly; and

a resistance element coupled with the first treadle and the second treadle, the resistance element comprising a pivotally supported bracket having a first section and a second section to either side of a pivot axle, a first cable coupled between the first treadle assembly and the first side, a first shock coupled between the first section and the frame, a second cable coupled between the second treadle and the second side, and a second shock coupled between the second section and the frame.

## 23. (Cancelled)

 (Currently Amended) An exercise apparatus for a user with a first foot and a second foot, the exercise device comprising:

a frame structure:

a first treadle assembly pivotally connected <u>at its rear</u> with the frame structure, the first treadle assembly including an endless belt;

a second treadle assembly pivotally connected <u>at its rear</u> with the frame structure, the second treadle assembly including a second endless belt:

an interconnection member operably connected with the first treadle assembly and with the second treadle assembly such that pivotal movement of the first treadle assembly in a first direction causes pivotal movement of the second treadle assembly in a second direction opposite of the first direction;

at least one resistance element operably associated with the interconnection member; and

whereby, during use of the exercise device, a first foot moves rearwardly and downwardly and a second foot moves forwardly and upwardly.

## 25.-35. (Cancelled)

36. (Previously Presented) The exercise device of claim 1 further comprising at least one motor arranged to rotate the endless belts.

Appl. No. 10/789,294 Reply to Office Action of October 17, 2007

- 37. (Previously Presented) The exercise device of claim 24 further comprising at least one motor arranged to rotate the endless belts.
- 38. (Previously Presented) The exercise device of claim 2, wherein the resistance element is positioned at least partially below at least one of the first treadle or the second treadle.